

QF-5135CB Specification

Name of Product	Conveyor Type 350 Steam DC Oven	
Model	QF-5135CB-R(L)-24H	
Voltage	415V 3ph 50/60Hz	
Power Consumption	20kW	
Rated Current	27.8A	
Breaker Capacity	75A/30mA	
Electric Cord	2PNCT 14(mm ²) 4Px3m (End terminal – Round shape)	
Heater Connection	Δ(delta) connection	
Working Steam Pressure	0.1 MPa	
Water feeding from outside	Softened water – Automatic feeding to the water tank in the appliance. (Direct connection with faucet • Through water softener)	
	Raw water – Direct connection with faucet or connecting with the forked inlet of water softener.	
Water feeding to steam tank	Feeding water by electromagnetic pump	
Drainage from steam tank	Automatic drainage by electric valve(Chilled water is automatically mixed in the drained water.)	
Diameters of pipe connections	Inlet of softened water	Dia.8mm hose joint
	Inlet of raw water	Dia.8mm hose joint
	Drain outlet for cooking area	25A(1B)
	Drain outlet for steam tank	20A(3/4B)
	Steam outlet for safety valve	20A(3/4B)
	Water tank overflow outlet	Dia.18mm x 12mm x 1m (hose) (from machine outlet)
Safety devices (Safety control)	Electro leakage breaker / Safety valve / Thermal protector for drive motor	
	Abnormal pressure detecting pressure switch	
	Safety pressure detecting pressure switch(at the time of drainage of the steam tank)	

	Emergency stop switch / Thermal protector for electromagnetic pump
	Detecting the steam tank heater being energized without soaked in the water.
	Prevention of excessive increase of superheated steam temperature / Prevention of excessive increase of cooking space heater temperature
Timer	Digital Countdown
Main part / Material quality	Stainless (SUS304, SUS316L, SUS430)
Cooking area	350(D) x 60(H)
Dimensions	1348(1305 – without tray)(W) x 645(D) x 1358(H)
Machine weight	190kg