

Technical parameters



Standing Type Cake Showcase								
Temp. Range	Model No.	Dimension (cm)	Voltage (V/Hz)	Power (W)	Capacity (L)	Layer	Refrigerant	N. W. (kg)
2°C ~ 8°C	R730V-M2	90*73*110	220V/50Hz	580	268	2	R134A	200
	R740V-M2	120*73*110		720	375	2	R134A	245
	R750V-M2	150*73*110		850	482	2	R134A	280
	R760V-M2	180*73*110		920	589	2	R134A	315
	R770V-M2	210*73*110		960	698	2	R134A	350
	R780V-M2	240*73*110		1096	809	2	R134A	405



Temp. Range	Model No.	Dimension (cm)	Voltage (V/Hz)	Power (W)	Capacity (L)	Layer	Refrigerant	N. W. (kg)
2°C ~ 8°C	G730A-W	90*78*124	220V/50Hz	725	305	3	R134A	190
	G740A-W	120*78*124		814	455	3	R134A	230
	G750A-W	150*78*124		990	605	3	R134A	270
	G760A-W	180*78*124		1192	705	3	R134A	310
	G770A-W	210*78*124		1270	805	3	R134A	350
	G780A-W	240*78*124		1360	905	3	R134A	390



Temp. Range	Model No.	Dimension (cm)	Voltage (V/Hz)	Power (W)	Capacity (L)	Layer	Refrigerant	N. W. (kg)
2°C ~ 8°C	RL730V-M2	90*73*120	220V/50Hz	580	370	3	R134A	215
	RL740V-M2	120*73*120		720	518	3	R134A	255
	RL750V-M2	150*73*120		850	666	3	R134A	295
	RL760V-M2	180*73*120		920	814	3	R134A	335
	RL770V-M2	210*73*120		960	962	3	R134A	375
	RL780V-M2	240*73*120		1096	1006	3	R134A	415



Temp. Range	Model No.	Dimension (cm)	Voltage (V/Hz)	Power (W)	Capacity (L)	Layer	Refrigerant	N. W. (kg)
2°C ~ 8°C	KI730A-M2	90*73*120	220V/50Hz	580	293	3	R134A	200
	KI740A-M2	120*73*120		720	443	3	R134A	240
	KI750A-M2	150*73*120		826	593	3	R134A	270
	KI760A-M2	180*73*120		920	743	3	R134A	320
	KI770A-M2	210*73*120		960	843	3	R134A	370
	KI780A-M2	240*73*120		1096	943	3	R134A	400



Temp. Range	Model No.	Dimension (cm)	Voltage (V/Hz)	Power (W)	Capacity (L)	Layer	Refrigerant	N. W. (kg)
2°C ~ 8°C	RL730A-M2	90*73*120	220V/50Hz	580	230	3	R134A	180
	RL740A-M2	120*73*120		720	306	3	R134A	220
	RL750A-M2	150*73*120		850	380	3	R134A	250
	RL760A-M2	180*73*120		920	450	3	R134A	290
	RL770A-M2	210*73*120		960	525	3	R134A	330
	RL780A-M2	240*73*120		1096	610	3	R134A	370



Temp. Range	Model No.	Dimension (cm)	Voltage (V/Hz)	Power (W)	Capacity (L)	Layer	Refrigerant	N. W. (kg)
2°C ~ 8°C	KI730AF-M2	90*73*131	220V/50Hz	480	293	3	R134A	200
	KI740AF-M2	120*73*131		620	443	3	R134A	240
	KI750AF-M2	150*73*131		726	593	3	R134A	270
	KI760AF-M2	180*73*131		820	743	3	R134A	320
	KI770AF-M2	210*73*131		960	843	3	R134A	370
	KI780AF-M2	240*73*131		1176	943	3	R134A	400