

Technical parameters



Temp. Range	Model No.	Dimension (cm)	Voltage (V/Hz)	Power (W)	Capacity (L)	Layer	Refrigerant	N. W. (kg)
2°C ~ 8°C	KT730A-M2	90*73*137	220V/50Hz	725	320	4	R134A	200
	KT740A-M2	120*73*137		814	470	4	R134A	240
	KT750A-M2	150*73*137		990	620	4	R134A	270
	KT760A-M2	180*73*137		1192	720	4	R134A	320
	KT770A-M2	210*73*137		1270	870	4	R134A	380
	KT780A-M2	240*73*137		1360	970	4	R134A	400



Temp. Range	Model No.	Dimension (cm)	Voltage (V/Hz)	Power (W)	Capacity (L)	Layer	Refrigerant	N. W. (kg)
2°C ~ 8°C	S730V-M	90*69*190	220V/50Hz	230	615	5	R134A	230
	S740V-M	120*69*190		270	840	5	R134A	270
	S750V-M	150*69*190		310	1065	5	R134A	310
	S760V-M	180*69*190		350	1290	5	R134A	350
	S770V-M	210*69*190		430	1440	5	R134A	430
	S780V-M	240*69*190		460	1640	5	R134A	460



Temp. Range	Model No.	Dimension (cm)	Voltage (V/Hz)	Power (W)	Capacity (L)	Layer	Refrigerant	N. W. (kg)
2°C ~ 8°C	KT730AF-M2	90*73*142	220V/50Hz	580	320	4	R134A	200
	KT740AF-M2	120*73*142		720	470	4	R134A	240
	KT750AF-M2	150*73*142		826	620	4	R134A	270
	KT760AF-M2	180*73*142		920	720	4	R134A	320
	KT770AF-M2	210*73*142		960	870	4	R134A	380
	KT780AF-M2	240*73*142		1096	970	4	R134A	400



Temp. Range	Model No.	Dimension (cm)	Voltage (V/Hz)	Power (W)	Capacity (L)	Layer	Refrigerant	N. W. (kg)
2°C ~ 8°C	S830A-M	90*82*110	220V/50Hz	174	216	2	R134A	165
	S840A-M	120*82*110		256	323	2	R134A	205
	S850A-M	150*82*110		602	430	2	R134A	245
	S860A-M	180*82*110		815	537	2	R134A	285
	S870A-M	210*82*110		862	651	2	R134A	335
	S880A-M	240*82*110		862	751	2	R134A	365



Temp. Range	Model No.	Dimension (cm)	Voltage (V/Hz)	Power (W)	Capacity (L)	Layer	Refrigerant	N. W. (kg)
2°C ~ 8°C	ST730V-M	90*69*160	220V/50Hz	725	516	4	R134A	205
	ST740V-M	120*69*160		814	705	4	R134A	245
	ST750V-M	150*69*160		990	894	4	R134A	275
	ST760V-M	180*69*160		1192	1083	4	R134A	315
	ST770V-M	210*69*160		1270	1261	4	R134A	355
	ST780V-M	240*69*160		1360	1461	4	R134A	395



Temp. Range	Model No.	Dimension (cm)	Voltage (V/Hz)	Power (W)	Capacity (L)	Layer	Refrigerant	N. W. (kg)
2°C ~ 8°C	RY830A-M2	90*82*120	220V/50Hz	174	295	3	R134A	208
	RY840A-M2	120*82*120		256	443	3	R134A	248
	RY850A-M2	150*82*120		602	591	3	R134A	288
	RY860A-M2	180*82*120		815	739	3	R134A	328
	RY870A-M2	210*82*120		1200	836	3	R134A	388
	RY880A-M2	240*82*120		1200	936	3	R134A	408